

AT150F1022/U

Attribute	Value
SKU Short Description	40 VA Multisystem Mount Transformer
Product Taxonomy Node	RMH Root.Electrical Components.Transformers
Linking Product Number	AT150
Bundle	No
Includes	1/2-14 NPSM conduit connector, Lock Nut, Mounting Feet
Secondary Connection Size	9 in 229 mm
Secondary Connection Type	Leadwires
Primary Connection Size	9 in 229 mm
Package Height UoM	in
Package Length UoM	in
Package Weight	2.1
Package Weight UoM	lb
Package Width UoM	in
Product Height	3.19
Product Height UoM	in
Product Length	2.19
Product Length UoM	in
Product Width	3.63
Product Width UoM	in
Color	Metallic
Mounting Type	Includes 1/2-14 NPSM conduit connector and lock nut for mounting on plate Panel (not included) with 7/8 in. knockout Mounting feet for surface mount
Application	Power To 24 VAC Circuits In Heating and Cooling Systems
Ambient Operating Temperature (Max)	105 °F 41 °C
Ambient Operating Temperature (Min)	-20 °F -29 °C
Frequency	60 Hz

Attribute	Value
Secondary Open Circuit Voltage	27 V.O.C.
Primary Input Voltage	120/208/240 V ac
VA Rating	50 VA
Phase	DNA
Approvals and Standards	UL Listed: File no. E14881, Guide no. XOKV Certified: File No. LR95329-18
SKU Title	AT150F1022 50 VA Multi Mount Transformer
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267151115
LOB	RTS