

AT88A1005/U

Attribute	Value
SKU Short Description	Foot mounted 120 V AC Transformer with 12 in Leadwires and internally fused secondary for overload protection.
Product Taxonomy Node	RMH Root.Electrical Components.Transformers
Linking Product Number	AT88
Bundle	No
Includes	Internally fused secondary for overload protection
Secondary Connection Size	12 in 305 mm
Secondary Connection Type	Leadwires
Primary Connection Size	12 in 305 mm
Primary Connection Type	Leadwires: Black/White
Package Height UoM	in
Package Length UoM	in
Package Weight	3.1
Package Weight UoM	lb
Package Width UoM	in
Product Height	2.22 56.4
Product Height UoM	in mm
Product Width	2.19 56
Product Width UoM	in mm
Mounting Type	Foot Mounted
Application	75 VA transformers powers 24 Vac air conditioning circuits and other applications that do not exceed the listed ratings.
Ambient Operating Temperature (Max)	105 °F 41 °C
Ambient Operating Temperature (Min)	-20 °F -29 °C
Frequency	50 Hz; 60 Hz
Secondary Open Circuit Voltage	26.5 V.O.C.

Attribute	Value
Primary Input Voltage	120 V ac
VA Rating	75 VA
Phase	DNA
Approvals and Standards	UL Component Recognized CSA Certified NEC Class 2
SKU Title	AT88A1005 Foot mounted 120 V AC Transformer with 12 in Leadwires
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267036368
LOB	RTS