

# C554A1794/U

| Attribute               | Value  |
|-------------------------|--|
| SKU Short Description   | Cadmium-Sulfide Flame Detector with 60 in lead   |
| Product Taxonomy Node   | RMH Root.Sensors.Flame Detectors   |
| Linking Product Number  | C554   |
| Bundle                  | No   |
| For Use With            | R4166 R4184 R8182 R8184 R8185 R8404 R8991 R7997 R7184 R7284  |
| Includes                | Type "E" mounting bracket Fuel line adaptor  |
| Product Features        | Replaceable CAD Cell On flame failure, the light sensitive cadmium sulfide cell, in conjunction with flame sensing circuitry, causes the Protectorelay® control to shutdown the main oil burner. |
| Lead Wire Length        | 60 in; 5 ft  |
| Package Height UoM      | in   |
| Package Length UoM      | in   |
| Package Weight          | 0.2  |
| Package Weight UoM      | lb   |
| Package Width UoM       | in   |
| Product Height          | 1.88 47  |
| Product Height UoM      | in mm  |
| Product Length          | 1 25   |
| Product Length UoM      | in mm  |
| Product Width           | 0.5 13   |
| Product Width UoM       | in mm  |
| Mounting Bracket Type   | Type R bracket   |
| Application             | Oil fired burners  |
| Approvals and Standards | UL Listed: File no. MP268, Vol. 39, Sec. 1, Guide MCCZ CSA Component Listed: File no. LR95329  |
| SKU Title               | Cadmium-Sulfide Flame Detector with 60 in. lead  |
| Brand                   | Resideo  |
| Global ERP Status Code  | 01   |

| Attribute  | Value        |
|------------|--------------|
| UPC Number | 085267037877 |
| LOB        | RTS          |