

# L4006B1007/U

| Attribute                 | Value  |
|---------------------------|--|
| SKU Short Description     | Circulator Aquastat Controller, Range 100-240 °F, 1/2 in NPT, fixed differential, SPST, contacts break on temperature rise |
| Product Taxonomy Node     | RMH Root.Controls.Aquastats  |
| Linking Product Number    | L4006B - Well  |
| Bundle                    | No   |
| Includes                  | 1/2 in Well - 123869A  |
| Capillary Length          | 1 1/2 in   |
| Bulb Diameter             | 3/8 in 10 mm   |
| Bulb Length               | 2 7/8 in 73 mm   |
| Package Height UoM        | mm   |
| Package Length UoM        | mm   |
| Package Weight            | 0.64   |
| Package Weight UoM        | kg   |
| Package Width UoM         | mm   |
| Product Height            | 5.63 143   |
| Product Height UoM        | in mm  |
| Product Width             | 2 51   |
| Product Width UoM         | in mm  |
| Insulation Depth          | 1.5 in   |
| Well Spud Size            | 1/2 in 14 NPT 13 mm 14 NPT   |
| Bulb Material             | Copper (Cu)  |
| Color                     | Gray   |
| Application               | Circulator Control   |
| Switch Action             | Contacts break on temperature rise   |
| Switch Type               | SPST   |
| Ambient Temperature (Max) | 150 °F 66 °C   |
| Differential Temperature  | 5 °F Fixed 3 °C Fixed  |

| Attribute                          | Value   |
|------------------------------------|---|
| Operating Temperature (Max)        | 240 °F 116 °C   |
| Operating Temperature (Min)        | 100 °F 38 °C  |
| Electrical Ratings at Full Load    | 8 A @ 120 V AC 5.1 A @ 240 V AC   |
| Electrical Ratings at Locked Rotor | 48 A @ 120 V AC 30.6 A @ 240 V AC   |
| Electrical Ratings Millivolt       | 0.25 A @ 0.25 to 12 V DC  |
| Approvals and Standards            | UL Component Recognized: File No. MP466, Vol. 6, Sec.1, Guide No. MBPR2 CSA Certified: File No. LR95329-1 AGA Certified |
| SKU Title                          | Circulator Aquastat, Range 100-240 °F, 1/2 in NPT, fixed differential   |
| Brand                              | Resideo   |
| Global ERP Status Code             | 01  |
| UPC Number                         | 085267048804  |
| LOB                                | RTS   |
| Hazardous Material Code            | E08   |
| Hazardous Material Description     | UN1294, Dangerous Goods in Excepted Quantities, Class 3   |