

L4008A1130/U

Attribute	Value
SKU Short Description	High or Low Limit Aquastat, Range 130-270 °F, adjustable differential, SPST, contacts break on temperature rise, remote bulb, 120 in capillary length
Product Taxonomy Node	RMH Root.Controls.Aquastats
Linking Product Number	L4008
Bundle	No
Includes	10 ft Capillary 3.04 m Capillary
Product Features	Stop factory- Set at 200 °F Stop factory- Set at 93 °C
Capillary Length	120 in
Bulb Diameter	3/8 in 10 mm
Bulb Length	2 7/8 in 73 mm
Package Height UoM	mm
Package Length UoM	mm
Package Weight	0.563
Package Weight UoM	kg
Package Width UoM	mm
Product Height	5.63 143
Product Height UoM	in mm
Product Width	2 51
Product Width UoM	in mm
Bulb Material	Copper (Cu)
Color	Gray
Application	High or Low Limit Control
Switch Action	Contacts break on temperature rise
Switch Type	SPST
Ambient Temperature (Max)	150 °F 66 °C
Differential Temperature	5 °F to 30 °F Adjustable 3 °C to 17 °C Adjustable
Operating Temperature (Max)	270 °F 132 °C

Attribute	Value
Operating Temperature (Min)	130 °F 54 °C
Electrical Ratings at Full Load	8 A @ 120 V AC 5.1 A @ 240 V AC
Electrical Ratings at Locked Rotor	48 A @ 120 V AC 30.6 A @ 240 V AC
Electrical Ratings Millivolt	0.25 A @ 0.25 to 12 V DC
Approvals and Standards	UL Component Recognized: File No. MP466, Vol. 6, Sec.1, Guide No. MBPR2 CSA Certified: File No. LR95329-1
SKU Title	Aquastat, Range 130-270 °F, adjustable differential, remote bulb
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267049078
LOB	RTS
Hazardous Material Code	E08
Hazardous Material Description	UN1294, Dangerous Goods in Excepted Quantities, Class 3