

# L4008B1013/U

Attribute	Value
SKU Short Description	Circulator Aquastat, Range 100-240 °F, adjustable differential, SPST, contacts break on temperature rise, remote bulb, 66 in capillary length
Product Taxonomy Node	RMH Root.Controls.Aquastats
Linking Product Number	L4008
Bundle	No
Includes	5 1/2 ft Capillary 1.7 m Capillary
Capillary Length	66 in
Bulb Diameter	3/8 in 10 mm
Bulb Length	2 7/8 in 73 mm
Package Height UoM	mm
Package Length UoM	mm
Package Weight	0.563
Package Weight UoM	kg
Package Width UoM	mm
Product Height	5.63 143
Product Height UoM	in mm
Product Width	2 51
Product Width UoM	in mm
Bulb Material	Copper (Cu)
Color	Gray
Application	Circulator Control
Switch Action	Contacts break on temperature rise
Switch Type	SPST
Ambient Temperature (Max)	150 °F 66 °C
Differential Temperature	5 °F to 30 °F Adjustable 3 °C to 17 °C Adjustable
Operating Temperature (Max)	240 °F 116 °C
Operating Temperature (Min)	100 °F 38 °C

Attribute	Value
Electrical Ratings at Full Load	8 A @ 120 V AC 5.1 A @ 240 V AC
Electrical Ratings at Locked Rotor	48 A @ 120 V AC 30.6 A @ 240 V AC
Electrical Ratings Millivolt	0.25 A @ 0.25 to 12 V DC
Approvals and Standards	UL Component Recognized: File No. MP466, Vol. 6, Sec.1, Guide No. MBPR2 CSA Certified: File No. LR95329-1
SKU Title	Circulator Aquastat, Range 100-240 °F, adjustable differential, remote bulb
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267049160
LOB	RTS
Hazardous Material Code	E08
Hazardous Material Description	UN1294, Dangerous Goods in Excepted Quantities, Class 3