

L4008E1305/U

Attribute	Value
SKU Short Description	High Limit Aquastat Controller, Range 100-240 °F, manual reset, SPST, contacts break on temperature rise, remote bulb, 66 in capillary length
Product Taxonomy Node	RMH Root.Controls.Aquastats
Linking Product Number	L4008
Bundle	No
Product Features	Stop factory- Set at 240 °F Stop factory- Set at 116 °C
Capillary Length	66 in
Bulb Diameter	3/8 in 10 mm
Bulb Length	2 7/8 in 73 mm
Package Height UoM	mm
Package Length UoM	mm
Package Weight	0.55
Package Weight UoM	kg
Package Width UoM	mm
Product Height	5.63 143
Product Height UoM	in mm
Product Width	2 51
Product Width UoM	in mm
Bulb Material	Copper (Cu)
Color	Gray
Mounting Type	Horizontal Mount Vertical Mount
Application	High Limit Control with Manual Reset
Switch Action	Contacts break on temperature rise
Switch Type	SPST - NC
Ambient Temperature (Max)	150 °F 66 °C
Differential Temperature	Manual Reset
Electrical Ratings at Full Load	8 A @ 120 V AC 5.1 A @ 240 V AC

Attribute	Value
Electrical Ratings at Locked Rotor	48 A @ 120 V AC 30.6 A @ 240 V AC
Electrical Ratings Millivolt	0.25 A @ 0.25 to 12 V DC
Approvals and Standards	UL Component Recognized: File No. MP466, Vol. 6, Sec.1, Guide No. MBPR2 CSA Certified: File No. LR95329-1
SKU Title	High Limit Aquastat, Range 100-240 °F, manual reset, remote bulb
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267136013
LOB	RTS
Hazardous Material Code	E08
Hazardous Material Description	UN1294, Dangerous Goods in Excepted Quantities, Class 3