

L6006A1012/U

Attribute	Value
SKU Short Description	Circulator Aquastat Controller, High or Low Limit, Range 100-240 °F, 1/2 in NPT, fixed differential, SPST, NO terminals break on temperature rise
Product Taxonomy Node	RMH Root.Controls.Aquastats
Linking Product Number	L6006
Bundle	No
Includes	1/2 in Well - 123869A
Capillary Length	1 1/2 in
Bulb Diameter	3/8 in 10 mm
Bulb Length	2 7/8 in 73 mm
Package Height UoM	mm
Package Length UoM	mm
Package Weight	0.64
Package Weight UoM	kg
Package Width UoM	mm
Product Height	5.63 143
Product Height UoM	in mm
Product Width	2 51
Product Width UoM	in mm
Insulation Depth	1.5 in
Well Spud Size	1/2 in 14 NPT 13 mm 14 NPT
Bulb Material	Copper (Cu)
Color	Gray
Mounting Type	Horizontal Mount Vertical Mount
Application	Circulator Control and High Limit or Low Limit
Switch Type	SPDT
Ambient Temperature (Max)	150 °F 66 °C
Differential Temperature	5 °F Fixed 3 °C Fixed

Attribute	Value
Electrical Ratings at Full Load	8 A @ 120 V AC 5.1 A @ 240 V AC
Electrical Ratings at Locked Rotor	48 A @ 120 V AC 30.6 A @ 240 V AC
Electrical Ratings Millivolt	0.25 A @ 0.25 to 12 V DC
Approvals and Standards	UL Component Recognized: File No. MP466, Vol. 6, Sec.1, Guide No. MBPR2 CSA Certified: File No. LR95329-1
SKU Title	Circulator Aquastat, High or Low Limit, Range 100-240°F, fixed differential
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267053686
LOB	RTS
Hazardous Material Code	E08
Hazardous Material Description	UN1294, Dangerous Goods in Excepted Quantities, Class 3