

# L6006A1145/U

Attribute	Value
SKU Short Description	High or low limit horizontal mount controller with SPDT, operating range 100-240F, 3 inch capillary.
Product Taxonomy Node	RMH Root.Controls.Aquastats
Linking Product Number	L6006
Bundle	No
Includes	Stop factory-set at 240 F (116 C) Heat Conductive Compound
Capillary Length	3 in
Bulb Length	3/8 in x 2 7/8 in
Package Height UoM	mm
Package Length UoM	mm
Package Weight	0.61
Package Weight UoM	kg
Package Width UoM	mm
Product Height	5.63
Product Height UoM	in
Product Length	2
Product Length UoM	in
Product Width	2.13
Product Width UoM	in
Bulb Material	Copper (Cu)
Color	Gray
Mounting Type	Horizontal Mount
Application	Circulator Control and High Limit or Low Limit
Switch Type	SPDT
Differential Temperature	5 °F to 30 °F Adjustable
SKU Title	Horizontal Mount Controller with SPDT - 100-240F
Brand	Resideo

Attribute	Value
Global ERP Status Code	01
UPC Number	085267053693
LOB	RTS
Hazardous Material Code	E08
Hazardous Material Description	UN1294, Dangerous Goods in Excepted Quantities, Class 3