

L6006A1244/U

Attribute	Value
SKU Short Description	Circulator Aquastat Controller, High or Low Limit, Range 100-240 °F, adjustable differential, SPST, NO terminals break on temperature rise
Product Taxonomy Node	RMH Root.Controls.Aquastats
Linking Product Number	L6006
Bundle	No
Capillary Length	3 in
Bulb Diameter	3/8 in 10 mm
Bulb Length	2 7/8 in 73 mm
Package Height	57
Package Height UoM	mm
Package Length	324
Package Length UoM	mm
Package Weight	0.563
Package Weight UoM	kg
Package Width	127
Package Width UoM	mm
Product Height	5.63 143
Product Height UoM	in mm
Product Width	2 51
Product Width UoM	in mm
Insulation Depth	3 in
Bulb Material	Copper (Cu)
Color	Gray
Mounting Type	Horizontal Mount Vertical Mount
Application	Circulator Control and High Limit or Low Limit
Ambient Temperature (Max)	150 °F 66 °C
Differential Temperature	5 °F to 30 °F Adjustable 3 °C to 17 °C Adjustable

Attribute	Value
Operating Temperature (Max)	240 °F 116 °C
Operating Temperature (Min)	100 °F 38 °C
Electrical Ratings at Full Load	8 A @ 120 V AC 5.1 A @ 240 V AC
Electrical Ratings at Locked Rotor	48 A @ 120 V AC 30.6 A @ 240 V AC
Electrical Ratings Millivolt	0.25 A @ 0.25 to 12 V DC
Approvals and Standards	UL Component Recognized: File No. MP466, Vol. 6, Sec.1, Guide No. MBPR2 CSA Certified: File No. LR95329-1
SKU Title	Circulator Aquastat, High or Low Limit, Range 100-240°F, adj differential
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267053723
LOB	RTS
Hazardous Material Code	E08
Hazardous Material Description	UN1294, Dangerous Goods in Excepted Quantities, Class 3