

L7224U1002/U

Attribute	Value
SKU Short Description	Universal Electronic Oil Aquastat with EnviraCOM communication
Product Taxonomy Node	RMH Root.Controls.Aquastats
Linking Product Number	L7224
Bundle	No
Product Features	Complies with 2012 Department of Energy Standards Diagnostic updates through easy-to-read LED displays ± 2° F accuracy and faster response times Adjustable high- and low-limit differential Outdoor reset functionality available with W8735S1000 and W8735Y1000 Provides multizone control Thermowell horizontal or vertical and flush mounting EnviraCOM™ communications enabled Compatible with W8735S3000 Alarm Module
Package Height	4.6
Package Height UoM	in
Package Length	8.1
Package Length UoM	in
Package Weight	2.7
Package Weight UoM	lb
Package Width	4.7
Package Width UoM	in
Product Height	7.13 181
Product Height UoM	in mm
Product Length	4.25 109
Product Length UoM	in mm
Product Width	2.63 67
Product Width UoM	in mm
Color	Gray
Mounting Type	Flush Mounted Remote Mount Well Mount Horizontal Mount Vertical Mount
Application	Oil Aquastat Controller
Switch Type	3 SPST: High and Low Limit, Circulator
Type of Fuel	Oil

Attribute	Value
High Limit Set point Temperature (Max)	240 °F 116 °C
High Limit Set point Temperature (Min)	130 °F 54 °C
Low Limit Set point Temperature (Max)	220 °F 104 °C
Low Limit Set point Temperature (Min)	110 °F 43 °C
High Limit Differential Temperature	5 °F to 20 °F Adjustable
Low Limit Differential Temperature	10 °F to 25 °F Adjustable
Operating Frequency	60 Hz
Operating Voltage	120 V AC
Electrical Ratings at Full Load	7.4 A at 120 V AC
Electrical Ratings at Locked Rotor	44.4 A Inrush
Approvals and Standards	UL Component Recognized Canadian UL Component Recognized 2012 Department of Energy Standards Compliant
SKU Title	L7224U1002 Multi-System Electronic Oil Aquastat With EnviraCOM
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267255431
LOB	RTS