

PV200/U

Attribute	Value
SKU Short Description	2 in NPT Connection SuperVent Air Eliminator
Product Taxonomy Node	RMH Root.Hydronic Components.Air Vents
Linking Product Number	PV
Bundle	No
For Use With	PV-001RP/U Replacement Vent Top Float Assembly PV-020RP/U Vent Top Replacement (New Style 90 Degree)
Connection Size	Bottom Inlet 1/2 in Bottom Inlet 12.7 mm
Connection Type	Female NPT
Product Features	Brass cap for system shutoff System can be air tested Adjustable Vent Top Collar Ring allows easier installation and application flexibility High Temperature Thermoplastic Float Stainless Steel Concentrator is a patented and more efficient way to eliminate air Brass Bottom Port for expansion tank mounting, ease of installation and maintenance
Package Height	133
Package Height UoM	in
Package Length	279
Package Length UoM	in
Package Weight	9.1
Package Weight UoM	lb
Package Width	210
Package Width UoM	in
Product Height	10.7 272
Product Height UoM	in mm
Product Weight	8 3.63
Product Weight UoM	lb kg
Product Width	2.5 63
Product Width UoM	in mm
Product Depth	4 in 102 mm
Pipe Size	2 in

Attribute	Value
Product Diameter	4 in maximum
DN Size	DN50
Body Material	Bronze
Color	Brass
Seal Material	EPDM Rubber
Float Material	TPX® Polymethylpentene (PMP)
Application	Residential or Commercial closed loop hydronic heating or chilled water systems
Operating Pressure (Max)	125 psi
Operating Temperature (Max)	239 °F 115 °C
Operating Temperature (Min)	0 °F -17.7 °C
Flow Coefficient	95 Cv
SKU Title	2 in NPT Connection SuperVent Air Eliminator
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267827973
LOB	Water