

R4222N1002/U

Attribute	Value
SKU Short Description	120 V General Purpose Relay with DPDT switching
Product Taxonomy Node	RMH Root.Electrical Components.Contactors & Relays
Linking Product Number	R4222
Bundle	No
Coil Connection Size	1/4 in 6 mm
Coil Connection Type	Double Quick Connects
Product Features	Molded terminal numbers and circuit diagram on top of relay provide easy identification for wiring and checking system operation Untaped coil assures cooler operation Laminated magnet construction for higher efficiency Base designed for easy replacement of competitive relays Plug compatible with Steveco 90-340 and Mars 90340
Package Height	130
Package Height UoM	in
Package Length	144
Package Length UoM	in
Package Weight	0.5
Package Weight UoM	lb
Package Width	130
Package Width UoM	in
Product Height	1.88 48
Product Height UoM	in mm
Product Length	2.38 60
Product Length UoM	in mm
Product Width	2.16 55
Product Width UoM	in mm
Mounting Type	Screw Mount
Application	Powerpile (millivoltage) applications Pilot duty applications Power pole applications
Switch Action	DPDT - Pilot Duty

Attribute	Value
Power Supply Frequency	50 Hz 60 Hz
Pilot Duty Rating	Minimum: 3 VA @ 24 V AC, 120 V AC, 480 V AC Maximum: 25 VA @ 24 V AC, Maximum: 125 VA @ 120 V AC, 240 V AC, & 480 V AC Resistive: 3 A @ 277 V AC (0.75 power factor) Resistive: 3 A @ 277 V AC (0.75 power factor)
Coil Rating Voltage	120 V ac
Operating Frequency	50 Hz 60 Hz
Number of Poles	2 Poles
Approvals and Standards	UL Listed: File No. E49809, Guide No. NKCR2 CSA Certified: File No. LR35066, Guide No. 184-N-13.13
SKU Title	120 V General Purpose Relay with DPDT switching
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267075961
LOB	RTS