

# R7284B1024/U

Attribute	Value
SKU Short Description	Electronic Oil Primary with 15 seconds lock out
Product Taxonomy Node	RMH Root.Controls.Oil Controls
Linking Product Number	R7284
Bundle	No
Package Height UoM	in
Package Length UoM	in
Package Weight	1.5
Package Weight UoM	lb
Package Width UoM	in
Product Height	2.5 63.5
Product Height UoM	in mm
Product Length	4.16 105.4
Product Length UoM	in mm
Product Width	4.34 110.5
Product Width UoM	in mm
Mounting Location	Junction Box on main burner
Application	Residential oil fired burners used in boilers Residential oil fired burners used in forced air furnaces Residential oil fired burners used in Water heaters
Timing Safety Switch	15 sec
Ambient Operating Temperature (Max)	147 °F 64 °C
Ambient Operating Temperature (Min)	-40 °F -40 °C
Electrical Ratings at Full Load	7.4 A @ 120 Vac; 3.7 a @ 240 Vac
Electrical Ratings at Locked Rotor	44.4 A @ 120 Vac; 22.2 A @ 240 Vac
Electrical Connection	Burner motor Oil Valve Ignition Cad cell Limit Thermostat Alarm
Approvals and Standards	UL Component Recognized cUL Component Recognized
Ignition Type	Interrupted

Attribute	Value
SKU Title	R7284B1024 Electronic Oil Primary w/15 sec lock out
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267336550
LOB	RTS