

R7284U1004/U

| Attribute | Value |
|------------------------------------|---|
| SKU Short Description | Multisystem Electronic Oil Primary |
| Product Taxonomy Node | RMH Root.Controls.Oil Controls |
| Linking Product Number | R7284U |
| Bundle | No |
| Product Features | 16 character two line tri-lingual display provides simple programming and diagnostics Error history and baseline readings provide system performance and trends on models with display EnviraCOM™ enabled for remote access via EnviraLINK™ |
| Package Height UoM | in |
| Package Length UoM | in |
| Package Weight | 1.5 |
| Package Weight UoM | lb |
| Package Width UoM | in |
| Product Height | 2.5 64 |
| Product Height UoM | in mm |
| Product Length | 4.16 105 |
| Product Length UoM | in mm |
| Product Width | 4.34 110.5 |
| Product Width UoM | in mm |
| Color | Black |
| Application | Residential oil fired burners used in boilers Residential oil fired burners used in forced air furnaces Residential oil fired burners used in Water heaters |
| Valve On Delay Timing | : 0–30 seconds |
| Type of Fuel | Oil |
| Timing Safety Switch | Settable 15, 30 or 45 sec. |
| Electrical Ratings at Full Load | 10 A @ 120 Vac 3.7 A @ 240 Vac |
| Electrical Ratings at Locked Rotor | 60 A @ 120 Vac 22.2 A @ 240 Vac |
| Approvals and Standards | UL and cUL Component Recognized |

| Attribute | Value |
|------------------------|---|
| Ignition Type | Interrupted Intermittent |
| SKU Title | R7284U1004 Multisystem Electronic Oil Primary |
| Brand | Resideo |
| Global ERP Status Code | 01 |
| UPC Number | 085267344708 |
| LOB | RTS |