

R8182D1079/U

Attribute	Value
SKU Short Description	Combination Protectorelay® and Hydronic Heating Control. Vertical mount
Product Taxonomy Node	RMH Root.Controls.Aquastats
Linking Product Number	R8182
Bundle	No
Includes	Auxiliary ZC and ZR terminals may be used to provide circulator zone control through an R845A Switching Relay Heat Conductive Compound Horizontal case
Package Height UoM	in
Package Length UoM	in
Package Weight	4.8
Package Weight UoM	lb
Package Width UoM	in
Product Height	7.13
Product Height UoM	in
Product Length	5.25
Product Length UoM	in
Product Width	3.44
Product Width UoM	in
Color	Black
Application	High or Low Limit Control
High Limit Set point Temperature (Max)	240 °F 116 °C
High Limit Set point Temperature (Min)	130 °F 54 °C
Low Limit Set point Temperature (Max)	220 °F 104 °C
Low Limit Set point Temperature (Min)	110 °F 43 °C
Sensor Type	Remote Bulb
SKU Title	R8182D1079 Combination Protectorelay® and Hydronic Heating Control

Attribute	Value
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267078269
LOB	RTS
Hazardous Material Code	E08
Hazardous Material Description	UN1294, Dangerous Goods in Excepted Quantities, Class 3