

R8184G4009/U

Attribute	Value
SKU Short Description	Protectorelay® Oil Burner Control with 45 Second Safety Timing
Product Taxonomy Node	RMH Root.Controls.Oil Controls
Linking Product Number	R8184G
Bundle	No
Includes	With an LED for lockout indication Manual trip level on safety switch to assure burner shutdown during servicing
Product Features	Solid state flame sensing circuit LED on terminal strip indicates system lockout Enclosed safety switch with external reset butto
Package Height	81
Package Height UoM	in
Package Length	119
Package Length UoM	in
Package Weight	1.2
Package Weight UoM	lb
Package Width	107
Package Width UoM	in
Product Height	4.38
Product Height UoM	in
Product Length	4.06
Product Length UoM	in
Product Width	2.94
Product Width UoM	in
Color	Gray
Mounting Location	Direct Mounting on Burner Housing 4 in x 4 in Junction Box
Application	Controls oil burner, oil valve and the ignition transformer in response to a call for heat
Type of Fuel	Oil
Manual Reset	Yes

Attribute	Value
Timing Safety Switch	45 sec
Ambient Operating Temperature (Max)	130 °F
Ambient Operating Temperature (Min)	-40 °F
Electrical Ratings at Full Load	7.4 A @ 102 V AC 3.7 A @ 240 V AC
Electrical Ratings at Locked Rotor	44.4 A @ 120 V AC 22.2 A @ 240 V AC
Approvals and Standards	UL Component Recognized; File no. MP268, Vol. 35 Sec. 1,3 CSA Certified; File no. LR95329-1
Ignition Type	Intermittent
SKU Title	Protectorelay® Oil Burner Control with 45 Second Safety Timing
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267990127
LOB	RTS