

R8184G4082/U

Attribute	Value
SKU Short Description	Protectorelay® Oil Burner Control with 45 seconds lock out timing
Product Taxonomy Node	RMH Root.Controls.Oil Controls
Linking Product Number	R8184G
Bundle	No
Package Height UoM	in
Package Length UoM	in
Package Weight	1.3
Package Weight UoM	lb
Package Width UoM	in
Product Height	4.38 111
Product Height UoM	in mm
Product Width	4.13 104
Product Width UoM	in mm
Product Depth	2.5 in 64 mm
Mounting Location	4 in x 4 in Junction Box Direct Mounting on Burner Housing
Application	Controls oil burner, oil valve and the ignition transformer in response to a call for heat
Timing Safety Switch	45 sec
Ambient Operating Temperature (Max)	130 °F 54 °C
Ambient Operating Temperature (Min)	-40 °F -40 °C
Electrical Ratings at Full Load	7.4 A @ 120 Vac; 3.7 a @ 240 Vac
Electrical Ratings at Locked Rotor	44.4 A @ 120 Vac; 22.2 A @ 240 Vac
Approvals and Standards	UL Component Recognized; File no. MP268, Vol. 35 Sec. 1,3 CSA Certified; File no. LR95329-1
Ignition Type	Intermittent
SKU Title	R8184G4082 Protectorelay® Oil Burner Control w/45 sec lock out timing

Attribute	Value
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267078696
LOB	RTS