

# R8228B1012/U

Attribute	Value
SKU Short Description	24 V General Purpose Relay with SPDT switching
Product Taxonomy Node	RMH Root.Electrical Components.Contactors & Relays
Linking Product Number	R8228
Bundle	No
Coil Connection Size	1/4 in 6 mm
Coil Connection Type	Double Quick Connects
Product Features	Molded terminal numbers and circuit diagram on top of relay provide easy identification for wiring and checking system operation Untaped coil assures cooler operation Laminated magnet construction for higher efficiency Base designed for easy replacement of competitive relays Double quick-connect coil terminals Plug compatible with Steveco 90-340 and Mars 90340
Package Height UoM	in
Package Length UoM	in
Package Weight	0.5
Package Weight UoM	lb
Package Width UoM	in
Product Height	1.88 48
Product Height UoM	in mm
Product Length	2.38 60
Product Length UoM	in mm
Product Width	2.16 55
Product Width UoM	in mm
Mounting Type	Screw Mount
Application	General purpose relays with power rated contacts only
Switch Action	SPDT
Ambient Operating Temperature (Max)	155 °F 68 °C
Ambient Operating Temperature (Min)	-20 °F -29°C

<b>Attribute</b>	<b>Value</b>
Power Supply Frequency	50 Hz 60 Hz
Coil Rating Voltage	24 V ac
Operating Frequency	50 Hz 60 Hz
Number of Poles	1 Pole
Approvals and Standards	UL Component Recognized CSA Approved
SKU Title	24 V General Purpose Relay with SPDT switching
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267079938
LOB	RTS