

R841E1068/U

Attribute	Value
SKU Short Description	24 V SPST switching Electric Heater Relay
Product Taxonomy Node	RMH Root.Electrical Components.Contactors & Relays
Linking Product Number	R841
Bundle	No
Includes	Enclosure w/conduit bushing and integral transformer; dual load
Coil Connection Type	Leadwire
Product Features	Operate with each cycle of the thermostat (4 to 6 cycles per hour) Each relay switches up to a 5,000 W load Contacts make and break in about 75 seconds Mount in any position Includes 1/2 in. (13 mm) male conduit bushing
Package Height UoM	mm
Package Length UoM	mm
Package Weight	1.043
Package Weight UoM	kg
Package Width UoM	mm
Product Height	3.87 98
Product Height UoM	in mm
Product Length	1.5 38
Product Length UoM	in mm
Product Width	2.81 71
Product Width UoM	in mm
Application	SPST switching Electric Heater Relay
Switch Action	SPST
Ambient Operating Temperature (Max)	150 °F 66 °C
Ambient Operating Temperature (Min)	-20 °F -29°C
Power Supply Frequency	50 Hz 60 Hz
Coil Rating Voltage	24 V ac

Attribute	Value
Operating Frequency	50 Hz 60 Hz
Number of Poles	1 Pole
Approvals and Standards	UL Listed CSA Certified
SKU Title	24 V SPST switching Electric Heater Relay
Brand	Resideo
Global ERP Status Code	08
UPC Number	085267081566
LOB	Comfort