

S688A1007/U

| Attribute | Value |
|-------------------------------|--|
| SKU Short Description | Sail Switch with 5 in wide sail |
| Product Taxonomy Node | RMH Root.Air Treatment.Sail Switch |
| Linking Product Number | S688 |
| Bundle | No |
| Product Features | Simplified installations with multi-speed fans, inaccessible air handlers, fan motors with voltage or phase different from controlled equipment; eliminated wiring to system fan. Polyester film sail mounted on a micro switch snap switch. Removable spring counterbalances sail to allow mounting in either vertical (up or down) or horizontal air flow. Top and bottom conduit knockouts for wiring convenience. Low air velocity switch operation makes at 250 fpm and breaks at 75 fpm. |
| Package Height | 46 |
| Package Height UoM | mm |
| Package Length | 89 |
| Package Length UoM | mm |
| Package Weight | 0.363 |
| Package Weight UoM | kg |
| Package Width | 53 |
| Package Width UoM | mm |
| Product Height | 2.94 59 |
| Product Height UoM | in mm |
| Product Width | 3.75 95 |
| Product Width UoM | in mm |
| Additional Dimensions Details | Sail Dimensions 5 in wide (max) 127 mm wide (max) 26.2 sq in of area 16903 mm ² |
| Application | Air Flow Switch |
| Switch Action | SPDT |
| Ambient Temperature (Max) | At Switches: 125°F At Switches: 52 °C At Sail: 170 °F At Sail: 77 °C |
| Approvals and Standards | UL Listed: File No. E4436, Guide No. XAPX. CSA Certified |
| SKU Title | S688A1007 Sail Switch with 5 in wide sail |

| Attribute | Value |
|------------------------|----------------|
| Brand | Honeywell Home |
| Global ERP Status Code | 01 |
| UPC Number | 085267084161 |
| LOB | Comfort |