S8910U3000/U

Attribute	Value
SKU Short Description	Universal Hot Surface Ignition Module
Product Taxonomy Node	RMH Root.Controls.Burner & Ignition Controls
Linking Product Number	S8910U
Bundle	No
Includes	White Rodgers adapter|Robertshaw ground lead|Four 1/4 in. female .032 quick connects|One 3/16 in. female .032 quick connect|Nine wire labels
Typical Ignition Hardware	Norton 201|Norton 271|Q354
Typical Gas Control	VR8205|VR8305
Product Features	Replaces over 800 White Rodgers, Robertshaw and Resideo or Honeywell hot surface ignition model|LED status indicator and microammeter ports for easy trouble shooting|For local (single rod) or remote (dual rod) rectification type flame sensing|Provides one or three ignition trials (four|Field selectable number of ignition trials and trial time based on unit being replaced|Igniter warm up time: 7 (12 seconds second and third trial), 17 (27 seconds second and third trial), 34, or 45 seconds
Package Height	3.125
Package Height UoM	in
Package Length	4.563
Package Length UoM	in
Package Weight	0.9
Package Weight UoM	lb
Package Width	6.5
Package Width UoM	in
Product Height	5.25|133
Product Height UoM	in|mm
Product Width	4.06|103
Product Width UoM	in|mm
Product Depth	1.94 in|49 mm
Mounting Type	Mounts in any position except with terminals up|Recommended mounting position is with terminals down to provide maximum protection from dripping water or dust accumulation

Attribute	Value
Application	Hot Surface Pilot Ignition
Interpurge	64 seconds
Lockout Timing	4 sec|7 sec
Type of Fuel	Natural Gas|LPG
Ambient Operating Temperature (Max)	165 °F|74 °C
Ambient Operating Temperature (Min)	-40 °F|-40 °C
Frequency	50 Hz|60 Hz
Operating Frequency	50 Hz|60 Hz
Operating Voltage	24 Vac
Igniter-Sensor Rod	Dual|Single
Approvals and Standards	CSA Design Certified
Maximum Valve Load	2A
Ignition Type	Direct Hot Surface
Ignition Trials To Lockout	1 or 3
Pre-Purge	32 sec
SKU Title	S8910U3000 Universal Hot Surface Ignition Module
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267647489
LOB	RTS