

S9200U1000/U

Attribute	Value
SKU Short Description	Universal Ignition Furnace Control
Product Taxonomy Node	RMH Root.Controls.Burner & Ignition Controls
Linking Product Number	S9200
Bundle	No
Typical Gas Control	Any 24Vac redundant, direct ignition gas control rated at 1.5A or less. Honeywell VR8205 recommended.
Package Height	4.25
Package Height UoM	in
Package Length	7.625
Package Length UoM	in
Package Weight	1.52
Package Weight UoM	lb
Package Width	5.625
Package Width UoM	in
Product Height	4.13
Product Height UoM	in
Product Length	6.13
Product Length UoM	in
Product Width	1.5
Product Width UoM	in
Number of LEDs	3
Application	Single stage warm air furnaces
Interpurge	60 Seconds
Postpurge	15 Seconds
Ambient Operating Temperature (Max)	175 °F
Ambient Operating Temperature (Min)	-40 °F

Attribute	Value
Operating Frequency	60 Hz
Igniter Voltage	120 Vac
HSI Warmup Time	17/27 or 30/30 seconds
Ignition Type	Direct Hot Surface
Ignition Trials To Lockout	3; 2 tries if flame is not sensed
Pre-Purge	30 seconds
SKU Title	S9200U1000 Universal Ignition Furnace Control
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267316149
LOB	RTS