

ST9120U1011/U

Attribute	Value
SKU Short Description	Universal Electronic Fan Timer
Product Taxonomy Node	RMH Root.Controls.Burner & Ignition Controls
Linking Product Number	ST9120
Bundle	No
Product Features	Replaces 40+ existing Resideo and Honeywell electronic fan timers Replaceable fuse DIP switch selectable heat and cool delay on and off times Electronic air cleaner and humidifier terminal connections Continuous low speed indoor air circulation
Package Height UoM	in
Package Length UoM	in
Package Weight	1.04
Package Weight UoM	lb
Package Width UoM	in
Product Height	1.5
Product Height UoM	in
Product Length	5.75
Product Length UoM	in
Product Width	4.5
Product Width UoM	in
Application	Integrates control of combustion blower and circulating fan operations for a gas warm air appliance
Postpurge	5 sec
Ambient Operating Temperature (Max)	175 °F 79 °C
Ambient Operating Temperature (Min)	-40 °F -40 °C
Power Supply Frequency	50 Hz 60 Hz
Operating Frequency	50 Hz 60 Hz
Supply Voltage	Low Voltage: 18 to 30 Vac Line Voltage: 120V (97-132 Vac) Line Voltage: 240V (196 – 264 Vac)

Attribute	Value
Operating Voltage	18 to 30 Vac
Air Cleaner Load Rating	0.8A maximum combined load at 115 V AC 0.4A maximum combined load at 230 V AC
Electrical Ratings	18 to 30 Vac
Combution Blower Load Rating	1.5A full load, 10A locked rotor at 115 Vac 0.75A full load, 5A locked rotor at 230 Vac (Reduce full load rating by humidifier [HUM] load.)
Humidifier Load Rating	0.8A maximum combined load at 115 V ac 0.4A maximum combined load at 230 Vac
Circulating Fan Load Rating for Heat-Cool Speed	15A full load, 30A locked rotor at 115 Vac 7.5A full load, 15A locked rotor at 230 Vac (Reduce full load rating by electronic air cleaner [EAC] load.)
Circulating Fan Load Rating for Optional Continuous Speed	8A full load, 16A locked rotor at 115 Vac 4A full load, 8A locked rotor at 230 Vac
Thermostat Load Rating	0.10A plus ignition system load
Approvals and Standards	UL Listed: Report MP466 CSA Certified: File No. LR95329-41
SKU Title	Universal Electronic Fan Timer
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267719582
LOB	RTS