

T87N1026/U

Attribute	Value
SKU Short Description	The Round® Manual Thermostat, Easy-to-See
Product Taxonomy Node	RMH Root.Controls.Thermostats
Linking Product Number	T87
Bundle	No
For Use With	For temperature control of hot water storage cylinders, high and low temperature limiting on water pipes, and automatic heat/cool changeover for 2-pipe fan-coil systems Water temperature control
Includes	6 in. (152 mm) cover ring and switch position labels
Terminal Designations	R, Rc, W, Y, G, O, B, C
Product Features	Surface mounting thermostat for applications with hot water storage cylinders or water pipes Version available for use as a cylinder thermostat in domestic hot water installations Version available for use as a pipe thermostat in fan-coil applications Version available for use as a pipe thermostat in frost protection applications Version available for use as a pipe thermostat to limit the supply water temperature in underfloor heating and solid fuel systems The S.P.D.T. switching action is accomplished by a snap-action MICRO SWITCH which is actuated by a bimetal temperature sensing element The desired temperature control point is set by the clearly scaled temperature selector on the front cover Wiring terminals are easily accessible Screwdriver slot temperature setting, with optional manual setting knob supplied CE approved
Package Height UoM	in
Package Length UoM	in
Package Weight	0.6
Package Weight UoM	lb
Package Width UoM	in
Product Height	79
Product Height UoM	mm
Product Length	44
Product Length UoM	mm
Product Weight UoM	kg
Product Width	54
Product Width UoM	mm

Attribute	Value
Display Size	1.73 sq in
Color	Premier White®
Mounting Type	Wall Mounted
Fan Switch	Auto-On
Application	Conventional Systems Heat Pumps with No Auxiliary Heat
Stages	1 Heat/1 Cool
Number of Fan Speeds	1
Number of Switch Steps	1 SPDT 230 V AC, 4 A resistive, 2 A inductive
Modes of Operation	Cooling Heating Emergency Heat
Set point Temperature (Max)	Heat: 90 F Cool: 99 F
Set point Temperature (Min)	Heat: 40 F Cool: 50 F
Shipping and Storage Temperature (Max)	70 °C
Shipping and Storage Temperature (Min)	0 °C
Frequency	50 Hz 60 Hz
Power Supply	Battery Powered Hardwired
Supply Voltage	20 to 30 V AC
Sensor Type	Thermistor
Approvals and Standards	CE L641 (product must be wired as shown for CE compliance)
SKU Title	The Round® Manual Thermostat, Easy-to-See
Brand	Honeywell Home
Global ERP Status Code	01
UPC Number	085267263634
LOB	Comfort
Hazardous Material Code	HS8
Hazardous Material Description	LITHIUM METAL BATTERIES in compliance with Section II of PI970