

TB7100A1000/U

Attribute	Value
SKU Short Description	MultiPRO™ 7000 Multispeed and Multipurpose Programmable/Non-programmable Thermostat
Product Taxonomy Node	RMH Root.Controls.Thermostats
Linking Product Number	TB7100
Bundle	No
Alerts and Reminders	Battery Replacement
Includes	3 Speed Fan Control and Configurable Sensor Input for Indoor Temperature Occupancy Sensor Changeover
Terminal Designations	R, Rc, W1, O/B,, Y, G, G2, G3, C, S1, S2
Product Features	Selectable programmable or non-programmable.; Includes 3 speed fan control and configurable sensor input for indoor temperature, occupancy sensor, or changeover
Package Height	2.3
Package Height UoM	in
Package Length	7.4
Package Length UoM	in
Package Weight	0.9
Package Weight UoM	lb
Package Width	5.4
Package Width UoM	in
Product Depth	1.5 in 38 mm
Display Size	3.75 sq in
Color	Premier White®
Mounting Location	Wall Internal
Mounting Type	Horizontal Mount
Sensor Location	Built-in
Fan Switch	Auto-On Fan Coil: HI-MED-LO-AUTO PTAC: HI-LO-AUTO
Application	Conventional Systems Heat Pump Systems Fan Coil Systems PTAC Systems

Attribute	Value
Stages	1 Heat/1 Cool Conventional Systems Up to 2 Heat/1 Cool Heat Pump Systems 2 or 4 pipe Fan Coil Systems Up to 2 Heat/1 Cool PTAC Systems
Switch Action	DPDT
Number of Fan Speeds	3
Switch Type	Relay
Modes of Operation	Heat Cool Auto Off
Ambient Operating Temperature (Max)	102 °F 39 °C
Ambient Operating Temperature (Min)	37 °F 2.8 °C
Set point Temperature (Max)	Heat: 90 °F Heat: 32 °C Cool: 99 °F Cool: 37 °C
Set point Temperature (Min)	Heat: 40 °F Heat: 4 °C Cool: 50 °F Cool: 10 °C
Shipping and Storage Temperature (Max)	120 °F 49 °C
Shipping and Storage Temperature (Min)	-20 °F -29 °C
Differential Temperature	± 1 °F ± 0.5 °C
Power Supply	Battery Powered Hardwired
Power Supply Frequency	50 Hz 60 Hz
Operating Frequency	50 Hz 60 Hz
Supply Voltage	20 to 30 V AC 750 mV
Sensor Type	Thermistor
Approvals and Standards	Meets the same requirements as UL-873
Battery Type	Alkaline
Power Source	Battery Operated Hardwired
SKU Title	MultiPRO™ 7000 Multispeed & Multipurpose Thermostat
Brand	Honeywell Home
Global ERP Status Code	01
UPC Number	085267676724
LOB	Comfort

Attribute	Value
Hazardous Material Code	HS8
Hazardous Material Description	LITHIUM METAL BATTERIES in compliance with Section II of PI970