

TB7220U1012/U

Attribute	Value
SKU Short Description	CommercialPRO 7000 Programmable Commercial Thermostat
Product Taxonomy Node	RMH Root.Controls.Thermostats
Linking Product Number	TB7220
Bundle	No
Terminal Designations	R, Rc, W (O/B), W2 (W1), Y, Y2, A, G, C, S1, S2
Product Features	Includes A terminal to enable an economizer or control a lighting panel when used as a time of day relay; Selectable programmable or non-programmable.
Package Height	2.3
Package Height UoM	in
Package Length	7.5
Package Length UoM	in
Package Weight	0.8
Package Weight UoM	lb
Package Width	5.5
Package Width UoM	in
Product Height	3.75 96
Product Height UoM	in mm
Product Width	6 152
Product Width UoM	in mm
Product Depth	1.38 in 35 mm
Color	Premier White®
Mounting Location	Wall Internal
Mounting Type	Horizontal Mount
Sensor Location	Built-in
Fan Switch	Auto-On
Application	Conventional Systems Heat Pump Systems Packaged RTU 24 VAC Heating and Cooling Systems

Attribute	Value
Stages	Up to 3 Heat/2 Cool Heat Pump Systems Up to 2 Heat/2 Cool Conventional Systems
Switch Action	SPDT
Number of Fan Speeds	1
Modes of Operation	Heat Cool Auto Off
Set point Temperature (Max)	Heat: 90 °F Heat: 32 °C Cool: 99 °F Cool: 37 °C
Set point Temperature (Min)	Heat: 40 °F Heat: 4 °C Cool: 50 °F Cool: 10 °C
Differential Temperature	± 1 °F ± 0.5 °C
Power Supply	Battery Powered Hardwired
Power Supply Frequency	50 Hz 60 Hz
Supply Voltage	20 to 30 V AC 750 mV
Sensor Type	Thermistor
Battery Type	Alkaline
Power Source	Battery Operated Hardwired
SKU Title	CommercialPRO 7000 Programmable Thermostat
Brand	Honeywell Home
Global ERP Status Code	01
UPC Number	085267266451
LOB	Comfort
Hazardous Material Code	HS8
Hazardous Material Description	LITHIUM METAL BATTERIES in compliance with Section II of PI970