

# TH1210U4001/U

Attribute	Value
SKU Short Description	FocusPRO® N100 Non-Programmable Thermostat 2H/1C Heat Pump + 1H/1C Conventional
Product Taxonomy Node	RMH Root.Controls.Thermostats
Linking Product Number	N100
Bundle	No
Alerts and Reminders	Battery Replacement Heat Pump Failure Memory Error Sensor Error Filter Change
For Use With	C7089U1006 wired outdoor sensor
Includes	Thermostat UWP wall plate Decorative cover plate with J-box adaptor Mounting hardware AA batteries Literature
Terminal Designations	RC, R, C, W, W2-AUX, Y, O/B, G, K, L, E, S
Package Height	6.25
Package Height UoM	in
Package Length	4.75
Package Length UoM	in
Package Weight	0.71
Package Weight UoM	lb
Package Width	2.31
Package Width UoM	in
Product Height	3.44 87
Product Height UoM	in mm
Product Width	5.13 130
Product Width UoM	in mm
Product Depth	1.188 in  29.5 mm
Display Size	4.09 sq. in.
Displayed Information	Mode Current Temperature Set Temperature Status Display Fan
Display Language	English
Color	White

Attribute	Value
Mounting Type	UWP Wall Plate
Fan Switch	Auto-On-Circ
Application	24 Vac systems, Up to 2H/1C heat pumps with aux heat (default). Up to 1H/1C conventional systems. Gas, Oil, Electric, Hot Water Radiant or Steam Systems. Dual fuel.
Stages	Up to 2H/1C heat pumps with aux heat (default): Up to 1H/1C conventional systems.
Switch Type	Relay
Modes of Operation	Heat Off Cool Auto Emergency Heat
Ambient Operating Temperature (Max)	120 °F 49 °C
Ambient Operating Temperature (Min)	32 °F 0 °C
Set point Temperature (Max)	Heat: 90 °F Cool: 99 °F Heat: 32 °C Cool: 37 °C
Set point Temperature (Min)	Heat: 32 °F Cool: 50 °F Heat: 0 °C Cool: 10 °C
Shipping and Storage Temperature (Max)	120 °F 49 °C
Shipping and Storage Temperature (Min)	-20 °F -29 °C
Differential Temperature	± 1 °F ± 0.5 °C
Frequency	60 Hz
Power Supply	Battery Hardwired
Supply Voltage	20 to 30 Vac
Operating Current	Heat: 0.02-1.0 A Cool: 0.02 A to 1.0 A running Fan: 0.02-.05 A
Battery Type	AA Alkaline
Power Source	Hardwired Battery Operated
SKU Title	FocusPRO® N100 Non-Programmable Thermostat2H/1C HeatPump+1H/1C Conventional
Brand	Honeywell Home
Global ERP Status Code	01
UPC Number	194159018570
LOB	Comfort