

THX1100W3/U

Attribute	Value
SKU Short Description	ElitePRO™ S1100 Smart Thermostat in White
Product Taxonomy Node	RMH Root.Controls.Thermostats
Linking Product Number	THX1100
Bundle	No
For Use With	THP9045A C-wire adapter C7189R3010-2 room sensor
Includes	ElitePRO S1100 Series Thermostat in White UWP® Wall Plate Decorative Cover Plate with J-Box Adapter Mounting hardware Literature
Wireless Connectivity	Redlink 3.0
Terminal Designations	R, RC, C, W, O/B, G, Y, Y2, W2-AUX, E, L-A, K
Product Features	Time-Based or Smart Away programming for energy efficiency Includes Onboard Radar Sensor Allows Air quality monitoring
Package Height UoM	in
Package Length UoM	in
Package Weight	0.824
Package Weight UoM	lb
Package Width UoM	in
Product Height	3.54 90
Product Height UoM	in mm
Product Weight	0.91
Product Weight UoM	lb
Product Width	5.25 133
Product Width UoM	in mm
Product Depth	0.96 in 24 mm
Display Size	5 sq. in
Displayed Information	Indoor Humidity Outdoor Temperature Time Current Setting Current Temperature Thermostat Controls Down Arrow Up Arrow
Display Language	Display selectable for English, French, or Spanish
Display Time Format	12 Hour (AM/PM)

Attribute	Value
Color	White
Mounting Location	Wall Junction Box
Mounting Type	Horizontal Mount Junction Box Wall surface UWP Mounting System
Fan Switch	Auto-On-Circ
Application	Residential or light commercial, 24 Vac systems; Gas, Oil, Electric Warm Air, Hydronic, Fan coil unit, PTAC. IAQ control.
Stages	Up to 4 Heat/2 Cool Heat Pump systems Up to 3 Heat/3 Cool for conventional systems
Number of Fan Speeds	Up to 3 Fan Speeds for Fan Coil Units
Modes of Operation	Heat Off Cool Auto Emergency heat
Ambient Operating Temperature (Max)	102 °F 39 °C
Ambient Operating Temperature (Min)	37 °F 3 °C
Set point Temperature (Max)	Heat: 90 °F Cool: 99 °F Heat: 32 °C Cool: 37 °C
Set point Temperature (Min)	Heat: 40 °F Cool: 50 °F Heat: 4.5 °C Cool: 10°C
Shipping and Storage Temperature (Max)	120 °F 49 °C
Shipping and Storage Temperature (Min)	-20 °F -29 °C
Power Supply	Hardwired
Power Supply Frequency	60 Hz
Supply Voltage	20 to 30 V AC
Dehumidity Set point (Max)	100 % RH
Dehumidity Set point (Min)	10 % RH
Humidity Set point (Max)	90 % RH
Humidity Set point (Min)	0 % RH
Configuration	900 MHz
Energy Star Certified	Yes
Power Source	Hardwired
SKU Title	ElitePRO™ S1100 Smart Thermostat in White

Attribute	Value
Brand	Honeywell Home
Global ERP Status Code	01
UPC Number	194159018945