

# TI040/U

Attribute	Value
SKU Short Description	Industrial Programmable Indoor and Outdoor Timer
Product Taxonomy Node	RMH Root.Switches.Light Switches
Linking Product Number	TI040
Bundle	No
Product Features	Heavy-duty weather-proof casing (NEMA 3R) ideal for outdoor use Programming protected during power outage for 30 days
Package Height UoM	in
Package Length UoM	in
Package Weight	2.4
Package Weight UoM	lb
Package Width UoM	in
Product Height	7.22 182
Product Height UoM	in mm
Product Length	6.22 158
Product Length UoM	mm
Product Width	2.87 73
Product Width UoM	in mm
Displayed Information	Mode Time Day Program
Color	Gray
Application	Industrial Indoor/Outdoor Timer
Ambient Operating Temperature (Max)	122 °F 50 °C
Ambient Operating Temperature (Min)	-4 °F -20 °C
Shipping and Storage Temperature (Max)	122 °F 50 °C
Shipping and Storage Temperature (Min)	-40 °F -40 °C
Operating Frequency	50 Hz 60 hZ

Attribute	Value
Operating Voltage	120 V 240 V
Electrical Ratings	Max Load - 30 A (resistive), 10 A (ballast) Inductive Load - 10 A @ 120/240 V AC Resistive Load - 3600 W (30 A @ 120 V AC) Resistive Load - 7200 W (30 A @ 240 V AC)
Electrical Connection	Terminals for #14 to #10 AWG wire Multiswitch (3-way) compatible
SKU Title	TI040 - Industrial Programmable Indoor and Outdoor Timer
Brand	Resideo
Global ERP Status Code	01
UPC Number	775264304033
LOB	Comfort