

# V8043A1003/U

Attribute	Value
SKU Short Description	24 Vac 1/2 in Flare N.C. Zone Valve
Product Taxonomy Node	RMH Root.Valves.Hydraulic Valves.Zone Valves
Linking Product Number	V8043A
Bundle	No
Includes	End switch enclosure Manual Opener
Connection Size	1/2 in
Connection Type	Flare
Lead Wire Length	18 in 457 mm
Package Height	96
Package Height UoM	mm
Package Length	154
Package Length UoM	mm
Package Weight	0.998
Package Weight UoM	kg
Package Width	126
Package Width UoM	mm
Product Height	4 102
Product Height UoM	in mm
Product Length	2.38 60
Product Length UoM	in mm
Product Width	4.69 118
Product Width UoM	in mm
DN Size	DN15
Color	Brass
Valve Plug Material	Buna-N (NBR) Rubber
Valve Body Material	Brass

Attribute	Value
Valve Seat Material	Brass
Valve Stem Material	Stainless Steel
Application	Hydronic Control
Valve Body Pattern	Two-way Straight Through
Valve Start Position	Closed
Differential pressure for close-off (Max)	20 psi 138 kPa
Static Pressure Rating	125 psi 862 kPa
Media Temperature (Max)	200 °F 93 °C
Media Temperature (Min)	50 °F 10 °C
Ambient Operating Temperature (Max)	125 °F 52 °C
Frequency	50 Hz 60 Hz
Power Consumption	7.7 VA
Voltage	24 Vac
Approvals and Standards	UL Listed: File MH11826
Flow Coefficient	3.5 Cv 3 Kvs
Media Restrictions	Not for use in systems containing dissolved oxygen, such as systems that have frequent source of makeup water
SKU Title	24 Vac 1/2 in Flare N.C. Zone Valve
Brand	Honeywell Home
Global ERP Status Code	01
UPC Number	085267109598
LOB	Water