

# VC8715AM1000/U

Attribute	Value
SKU Short Description	24V Sweat VC Valves with Aux Switch
Product Taxonomy Node	RMH Root.Valves.Hydraulic Valves.Zone Valves
Linking Product Number	VC8715
Bundle	No
Includes	Valve VCZAM1100 Actuator VC8715ZZ11 Aux Switch
Valve Type	Zone Valve Three-way
Connection Type	Sweat
Product Features	Use with two-way or three-way valves Double insulated actuator Five foot plenum-rated cable Quick and easy replacement of moving parts Actuator head installation does not require draining the system Selectable/switchable electronic fail safe normally open or normally closed Available with valve bodies with 1000-series 2-way and 6000-series 3-way cartridges for new construction All VC Series actuator-valve combinations provide 60 psi close-off
Package Height	130
Package Height UoM	mm
Package Length	120
Package Length UoM	mm
Package Weight	0.953
Package Weight UoM	kg
Package Width	60
Package Width UoM	mm
Product Height	2.38 113
Product Height UoM	in mm
Product Length	3.5 94
Product Length UoM	in mm
Product Width	2.75 68
Product Width UoM	in mm
Valve Stem Length	10 mm
Valve Stem Travel	0.4 in 10 mm

Attribute	Value
DN Size	DN20
Color	Bronze
Valve Body Material	Bronze
Valve Seat Material	EPDM
Valve Stem Material	Stainless Steel
Fail-Safe Operation Type	Stays in place
Valve Body Pattern	Three-way
Valve Flow Characteristic	Quick Opening
Differential pressure for close-off (Max)	60 psi 400 kPa
Operating Pressure (Max)	300 psi 2068 kPa (20 Bar)
Media Temperature (Max)	203 °F 95 °C
Media Temperature (Min)	34 °F 1 °C
Ambient Operating Temperature (Max)	150 °F 65 °C
Ambient Operating Temperature (Min)	32 °F 0 °C
Shipping and Storage Temperature (Min)	-40 °F -40 °C
Frequency	60 Hz
Power Consumption	6 VA
Voltage	24 Vac
Electrical Connection Length	39 in 1 m
Electrical Connection Type	Cable
Flow Coefficient	5.8 Cv 5.0 Kvs
SKU Title	VC8715AM1000 24V Sweat VC Valves with Aux Switch
Brand	Honeywell Home
Global ERP Status Code	01
UPC Number	085267819657
LOB	Water