

VR8205H1003/U

Attribute	Value
SKU Short Description	Single Stage Gas Controls for Direct Ignition appliance, 1/2 in x 1/2 in inlet/outlet size, Slow Opening, 24 V AC, Natural Gas
Product Taxonomy Node	RMH Root.Valves.Fuel Control Valves.Gas Valves
Linking Product Number	VR8205
Bundle	No
For Use With	S89C S89E S89F S87 Series 5 and later
Regulator	Slow
Inlet Connection Size	1/2 in
Pilot Gas Outlet	None
Pressure Tap Connection Size	1/8 in
Pressure Tap Connection Type	NPT with Plug
Outlet Connection Size	1/2 in
Product Features	ON-OFF Lighting Sequence
Package Height	12
Package Height UoM	in
Package Length	14
Package Length UoM	in
Package Weight	1.8
Package Weight UoM	lb
Package Width	7
Package Width UoM	in
Product Height	4.94 125
Product Height UoM	in mm
Product Width	4.13 104
Product Width UoM	in mm
Color	Black Gray

Attribute	Value
Mounting Type	0° to 90° in any direction from the upright position of the gas control knob, including vertically
Application	Single-Stage Slow Opening Valve for Direct Burner Ignition
Valve Body Pattern	Straight Through
Type of Fuel	Natural Gas
Body Pressure Rating (Max)	3.5 kPa 1/2 psi
Operating Pressure (Max)	1/2 psi 3.5 kPa
Pressure Regulator Set point	3.5 in WC 0.87 kPa
Ambient Operating Temperature (Max)	175 °F 79 °C
Ambient Operating Temperature (Min)	0 °F -18 °C
Operating Frequency	60 Hz
Operating Voltage	24 V AC
Electrical Connection Type	Quick-Connect Male Terminals
Electrical Connection Size	1/4 in
Approvals and Standards	UL Component Recognized MCCZ2.MH5323 CSA International: 112395 Australian Gas Association: 4752
Regulation Type	Slow Opening
Universal	No
Capacity (Max)	200,000 BTU/h Natural Gas
Capacity (Min)	20,000 BTU/h Natural Gas
Capacity at 1in. wc p.d.	150,000 BTU/h Natural Gas
Appliance Capacity (Max)	415 cfh
Appliance Capacity (Min)	30 cfh
Ignition Type	Direct Burner Ignition
SKU Title	Single Stage, Standing Pilot, 1/2 in x 1/2 in, 24 V AC, Standard Opening
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267113403

Attribute	Value
LOB	RTS