

# VR8345H4555/U

Attribute	Value
SKU Short Description	Dual Direct Ignition/Intermittent Pilot
Product Taxonomy Node	RMH Root.Valves.Fuel Control Valves.Gas Valves
Linking Product Number	VR8345 Universal
Bundle	No
For Use With	Direct spark ignition Hot surface ignition Intermittent pilot ignition
Includes	Natural to LP Conversion Kit Two 3/4 in x 1/2 in Reducer Bushings
Inlet Connection Size	3/4 in
Pressure Tap Connection Size	1/8 in
Pressure Tap Connection Type	NPT with plug
Outlet Connection Size	3/4 in
Package Height UoM	in
Package Length UoM	in
Package Weight	1.8
Package Weight UoM	lb
Package Width UoM	in
Product Height	5.38
Product Height UoM	in
Product Length	2.69
Product Length UoM	in
Product Width	4.06
Product Width UoM	in
Mounting Type	0° to 90° in any direction from the upright position of the gas control knob, including vertically
Application	Slow Opening with Convertible Ignition
Valve Body Pattern	Straight Through
Type of Fuel	Natural Gas LP with included conversion kit
Pressure Regulator Set point	3.5 in WC 0.87 kPa

Attribute	Value
Ambient Operating Temperature (Max)	175 °F 79 °C
Ambient Operating Temperature (Min)	0 °F -18 °C
Operating Frequency	60 Hz
Operating Voltage	24 V AC
Electrical Connection Type	Quick Connect Male Terminals
Electrical Connection Size	1/4 in
Regulation Type	Slow Opening
Universal	No
Capacity (Min)	30,000 BTU/h
Capacity at 1in. wc p.d.	300,000 BTU/h
Ignition Type	Intermittent Pilot Direct Burner ignition
SKU Title	Dual Direct Ignition and Intermittent Pilot
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267797313
LOB	RTS