

# VR8345M4302/U

Attribute	Value
SKU Short Description	Direct spark ignition, hot surface ignition, or intermittent pilot ignition
Product Taxonomy Node	RMH Root.Valves.Fuel Control Valves.Gas Valves
Linking Product Number	VR8345 Universal
Bundle	No
For Use With	Natural, manufactured, or liquefied petroleum gas
Includes	Two 3/4 in x 1/2 in Reducer Brushings Natural to LP Gas Conversion Kit
Regulator	Standard
Inlet Connection Size	3/4 in
Pilot Gas Outlet	Compression fitting for 1/4 in. OD tubing
Pressure Tap Connection Size	1/8 in
Pressure Tap Connection Type	NPT with plug
Outlet Connection Size	3/4 in
Package Height	250
Package Height UoM	in
Package Length	212
Package Length UoM	in
Package Weight	2
Package Weight UoM	lb
Package Width	184
Package Width UoM	in
Product Height	5.38
Product Height UoM	in
Product Length	2.69
Product Length UoM	in
Product Width	4.06
Product Width UoM	in

Attribute	Value
Mounting Type	0° to 90° in any direction from the upright position of the gas control knob, including vertically
Application	Slow Opening with Convertible Ignition
Valve Body Pattern	Straight Through
Type of Fuel	Natural Gas LP with included conversion kit
Pressure Regulator Set point	3.5 in WC 0.87 kPa
Ambient Operating Temperature (Max)	175 °F 79 °C
Ambient Operating Temperature (Min)	-40 °F -40 °C
Operating Frequency	50 Hz 60 Hz
Operating Voltage	24 V AC
Electrical Connection Type	Quick Connect Male Terminals
Electrical Connection Size	1/4 in
Regulation Type	Standard Opening
Universal	Yes
Capacity (Max)	415,000 BTU/h Natural Gas
Capacity (Min)	30,000 BTU/h Natural Gas
Capacity at 1in. wc p.d.	300,000 BTU/h Natural Gas
Ignition Type	Intermittent Pilot Direct Burner ignition
SKU Title	Multisystem Intermittent Direct Ignition 24 V Standard Opening Gas Valve
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267780117
LOB	RTS