

VR9205Q1507/U

Attribute	Value
SKU Short Description	Two Stage Gas Controls for Direct Ignition appliance, 1/2 in x 1/2 in, Standard Opening, 24 V AC, Natural Gas/LP with included conversion kit
Product Taxonomy Node	RMH Root.Valves.Fuel Control Valves.Gas Valves
Linking Product Number	VR9205Q
Bundle	No
Includes	6 in Wire Harness LP Conversion Kit
Regulator	Adjustment Range: 0.9 in WC to 4.0 in WC
Inlet Connection Size	1/2 in
Outlet Connection Size	1/2 in
Package Height	4.063
Package Height UoM	in
Package Length	6.313
Package Length UoM	in
Package Weight	2
Package Weight UoM	lb
Package Width	5.188
Package Width UoM	in
Product Height	4.04 103
Product Height UoM	in mm
Product Length	5.04 128
Product Length UoM	in mm
Product Width	4.04 103
Product Width UoM	in mm
Color	Gray Black
Mounting Type	Any
Application	Two-Stage Standard Opening Valve for Direct Burner Ignition
Valve Body Pattern	Straight Through

Attribute	Value
Type of Fuel	Natural Gas LP with included conversion kit
Body Pressure Rating (Max)	1/2 psi 3.5 kPa
Operating Pressure (Max)	1/2 psi
Pressure Regulator Set point	High: 3.5 in WC; Low: 1.7 in WC High: 0.87 kPa; Low: 0.42 kPa
Ambient Operating Temperature (Max)	175 °F 79 °C
Ambient Operating Temperature (Min)	-40 °F -40 °C
Operating Frequency	50 Hz 60 Hz
Operating Voltage	24 V AC
Electrical Connection Type	Quick-Connect Male Terminals
Electrical Connection Size	1/4 in
Approvals and Standards	CSA International: 112491
Regulation Type	Standard Opening
Universal	No
Capacity (Max)	200,000 BTU/h at max fire
Capacity (Min)	8,000 BTU/h at low fire 200,000 BTU/h at high fire
Capacity at 1 in. wc p.d.	140,000 BTU/h
Ignition Type	Direct Burner Ignition
SKU Title	Two Stage, Direct Ignition, 1/2 in x 1/2 in, 24 V AC, Standard Opening
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267873512
LOB	RTS