

# Y8610U6006/U

Attribute	Value
SKU Short Description	Converts atmospheric standing pilot gas systems to intermittent pilot. Max capacity of 270 kBtuh
Product Taxonomy Node	RMH Root.Controls.Burner & Ignition Controls
Linking Product Number	S8610U
Bundle	Yes
Includes	VR8304M3558 gas valve Ignition module Pilot burner hardware Ignition cable Wiring harness
Typical Gas Control	VR8204, VR8304
Product Features	For use with natural or LP gas Provides ignition sequencing, flame monitoring and safety shutoff for intermittent pilot warm air furnaces and heating appliances
Package Height	4
Package Height UoM	in
Package Length	7
Package Length UoM	in
Package Weight	3.2
Package Weight UoM	lb
Package Width	6
Package Width UoM	in
Product Height	3.94
Product Height UoM	in
Product Length	5.44
Product Length UoM	in
Product Width	2.63
Product Width UoM	in
Application	Pilot Ignition
Lockout Timing	15 or 90 seconds
Type of Fuel	Natural Gas LPG
Frequency	60 Hz

Attribute	Value
Operating Voltage	24 Vac
Maximum Valve Load	1A Pilot 2A Main @ 24Vac
Ignition Type	Intermittent Pilot
Pre-Purge	0 or 30 seconds
SKU Title	Y8610U6006 270 kBtuh Intermittent Pilot Retrofit Kit
Brand	Resideo
Global ERP Status Code	01
UPC Number	085267311526
LOB	RTS