

YTH6320R1023/U

Attribute	Value
SKU Short Description	Wireless Programmable FocusPRO® Kit with Wireless Adapter allows to be used with TrueZONE panel
Product Taxonomy Node	RMH Root.Controls.Thermostats
Linking Product Number	TH6320R
Bundle	Yes
Alerts and Reminders	Battery Replacement High Indoor Temperature Low Indoor Temperature
For Use With	HZ322 or HZ432 TrueZONE® Panels
Includes	TH6320R1004 Wireless FocusPRO® 5-1-1 Programmable Thermostat THM4000R1000 Wireless Adapter
Terminal Designations	C, R, Rc, Rh, W-O/B, W2-Aux/E, Y, Y2, G, L, RAS
Product Features	<p>WIRELESS FOCUSPRO® THERMOSTAT: Same great features of the FocusPRO® thermostat - now wireless. Installs in minutes. Displays outdoor temperature and humidity. 1 year battery life. 2 month low battery warning. Dual Fuel enabled EQUIPMENT INTERFACE MODULE(EIM): All HVAC equipment is wired to the module. Module receives communication from the wireless devices RETURN AIR SENSOR: Works with the Equipment Interface Module to maintain safe indoor temperatures if power is lost at the wireless thermostat. Maintains 62 F for heating and 82 F for cooling REDLINK® WIRELESS TECHNOLOGY: Powered by RedLINK™ reliability. No interference with other wireless devices in the home.</p>
Capillary Length	Not Applicable
Bulb Diameter	Not Applicable
Bulb Length	Not Applicable
Capillary Diameter	Not Applicable
Package Height UoM	in
Package Length UoM	in
Package Weight	1.5
Package Weight UoM	lb
Package Width UoM	in
Product Height	3.56 91
Product Height UoM	in mm
Product Width	5.81 147

Attribute	Value
Product Width UoM	in mm
Product Depth	1.5 in 38 mm
Display Size	2.67 sq in
Displayed Information	Indoor Humidity Indoor Temperature Outdoor Humidity Outdoor Temperature Status Display
Display Language	English
Color	Premier White®
Mounting Location	Wall Internal
Mounting Type	Horizontal Mount
Sensor Location	Built-in
Fan Switch	Auto-On
Application	Conventional Systems Heat Pumps with Auxiliary Heat
Stages	Up to 3 Heat/2 Cool Heat Pump Systems Up to 2 Heat/2 Cool Conventional Systems
Number of Fan Speeds	1
Scale Markings	Not Applicable
Modes of Operation	Heat Cool Auto Off Emergency Heat
Ambient Operating Temperature (Max)	120 °F 49 °C
Ambient Operating Temperature (Min)	32 °F 0 °C
Interstage Differential Temperature	1 to 1.5 °F
Set point Temperature (Max)	Heating: 90 °F Cooling: 99 °F Heating: 32 °C Cooling: 37 °C
Set point Temperature (Min)	Heating: 40 °F Cooling: 50 °F Heating: 4.5 °C Cooling: 10 °C
Shipping and Storage Temperature (Max)	120 °F 49 °C
Shipping and Storage Temperature (Min)	-20 °F -29 °C
Differential Temperature	± 1 °F ± 0.5 °C
Power Supply	Battery
Operating Voltage (Max)	24 Vac

Attribute	Value
Electrical Connection Type	Screw terminals
Sensor Type	Thermistor
Energy Star Certified	No
SKU Title	Thermostat and adapter for RedLINK® Zone panels
Brand	Honeywell Home
Global ERP Status Code	01
UPC Number	085267331258
LOB	Comfort