

YTHX9421R5127WW/U

Attribute	Value
SKU Short Description	Prestige® IAQ Kit plus Redlink™ Internet Gateway
Product Taxonomy Node	RMH Root.Controls.Thermostats
Linking Product Number	THX9421R
Bundle	Yes
For Use With	RedLINK® accessories
Includes	THX9421R5021WW Prestige® 2-Wire IAQ Thermostat THM5421R1021 Equipment Interface Module THM6000R7001 RedLINK® Internet Gateway 2 Duct Sensors
Terminal Designations	C, R, Rc, Rh, W-O/B, W2-Aux/E, Y, Y2, G, L, RAS
Package Height	4.625
Package Height UoM	in
Package Length	10.25
Package Length UoM	in
Package Weight	2.5
Package Weight UoM	lb
Package Width	6.125
Package Width UoM	in
Product Height	4.06 104
Product Height UoM	in mm
Product Width	4.06 104
Product Width UoM	in mm
Product Depth	1.09 in 28 mm
Display Size	8.06 sq in
Display Language	Display selectable for English, French, or Spanish
Color	Front: White, Side: White
Fan Switch	Auto-On
Application	24 Vac systems; Gas, Oil, Electric Warm Air; Hot water Coil; Gas, Oil, Electric Hydronic; or Steam / Gravity Systems

Attribute	Value
Stages	Up to 4 Heat/2 Cool Heat Pump Systems Up to 3 Heat/2 Cool Conventional Systems
Number of Fan Speeds	1
Modes of Operation	Heating Cooling
Ambient Operating Temperature (Max)	120 °F 49 °C
Ambient Operating Temperature (Min)	32 °F 0 °C
Interstage Differential Temperature	1 to 1.5 °F 0.5 to 1°C
Shipping and Storage Temperature (Max)	120 °F 49 °C
Shipping and Storage Temperature (Min)	-20 °F -29 °C
Differential Temperature	± 1 °F ± 0.5 °C
Frequency	50 Hz 60 Hz
Power Supply	Battery Powered
Supply Voltage	18 to 30 V AC
Sensor Type	Thermistor
Energy Star Certified	Yes
Battery Type	Lithium Ion
SKU Title	YTHX9421R5127WW Basic Prestige Kit plus RedLINK® Internet Gateway
Brand	Honeywell Home
Global ERP Status Code	01
UPC Number	085267136945
LOB	Comfort
Hazardous Material Code	A22
Hazardous Material Description	Lithium metal button cells only contained in equipment, Excepted per PI970