

## Item Number: EX11DTN

Attribute	Value
Featured Image	<a href="https://rinnai.widen.net/content/tu0yvhtzww/web/EX08_Beige_Right.png?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/tu0yvhtzww/web/EX08_Beige_Right.png?u=vmp7gq&amp;download=true</a>
Product Category	Heating Systems>Direct Vent Wall Furnaces>EX DT Series
Active for Ecommerce	Yes
AFUE % Rating	0.81
Approved Use in	Mobile Home
Audience	Residential
Automatic Shutoff	Yes
Available to Order Date	2022-07-01
AvidWidgetDiv1	7423BTF
California Energy Commission (CEC) Model Registration Number	EX11DT (RHFE-266FTA)
Cascading (Y/N)	No
Central Heating Capacity	11,000 BTU / (3.2 kW)
Central Heating Heat Exchanger Material	STAINLESS STEEL
Central Heating Input (Btu&kW) - Maximum	11,000 BTU / (3.2 kW)
Certifications	CSA
Certified CSA	Yes
Certified MEA Massachusetts	Yes
Clearance from Combustibles (Back)	0" / (0 mm)
Clearance from Combustibles (Bottom)	0" / (0 mm)
Clearance from Combustibles (From vent pipe)	1" / (25 mm)
Clearance from Combustibles (Front)	40" / (1016 mm)
Clearance from Combustibles (Sides)	2" / (51 mm)
Clearance from Combustibles (Top)	0" / (0 mm)
Clearance from Non-Combustibles (Back)	0" / (0 mm)
Clearance from Non-Combustibles (Bottom)	0" / (0 mm)
Clearance from Non-Combustibles (From vent pipe)	0" / (0 mm)
Clearance from Non-Combustibles (Front)	40" / (1016 mm)
Clearance from Non-Combustibles (Sides)	2" / (51 mm)
Clearance from Non-Combustibles (Top)	0" / (0 mm)
Color	Beige
Country of Origin	Japan
Disclaimer	Capable of heating your whole home or complementing your existing heating system
Domestic Hot Water Natural Gas (Btu/kW) - Input Minimum	5,500 BTU / (1.6 kW)
Electrical Consumption (Maximum)	44W

Attribute	Value
Electrical Consumption (Normal)	44 watts
Electrical Voltage	AC 120 Volts, 60 Hz
Energy / Fuel Type	Natural Gas
Energy Star - Commercial	No
Energy Star - Residential	No
Fan Output - High (CFM)	128.5
Fan Output - Low (CFM)	96.4
Feature/Benefit Bullet 1	Input Range 5,500 - 11,000 BTU/hr
Feature/Benefit Bullet 2	Capable of heating your whole home or complementing your existing heating system (Heating area varies by geographic region and location of install within the home)
Feature/Benefit Bullet 3	Save energy – and money with Rinnai's modulating technology which produces the specific level of heat needed.
Feature/Benefit Bullet 4	Programmable Thermostat in Celsius or Fahrenheit that consistently detects temperature changes of less than 1 degree
Feature/Benefit Bullet 5	Control panel locking feature prevents unintended operation – especially by children.
Feature/Benefit Bullet 6	Cool-to-the-touch cabinet keeps you and your family safe
Feature/Benefit Bullet 7	Onboard self-diagnostics ensure your heater is performing optimally and simplifies troubleshooting if maintenance or service is needed.
Feature/Benefit Bullet 8	Professional installation recommended
Feature/Benefit Bullet 9	10-Year Heat Exchanger Warranty, 5 Year Parts, 2 Years Labor
Gas Supply Connection	1/2" FNPT / (13mm)
Hazmat Y/N	No
Heated Area (Sq. Ft.)	427.0
Heating - Fuel Gage Available	No
Heating - Remote Control Available	No
Heating - Timer Available	Yes
Heating Input Natural Gas (Btu/h &kW) - Maximum	11,000 BTU / (3.22 kW)
Heating Input Natural Gas (Btu/h &kW) - Minimum	5,500 BTU / (1.6 kW)
Heating Technology Type	Convection
Heating Temperature Range (Commercial) (°F/°C)	60-80°F
Heating Temperature Range (Residential) (°F/°C)	60-80°F
Ignition System	Direct Electronic Ignition
Image - Corporate Logo	<a href="https://rinnai.widen.net/content/bjw5z2ex3z/web/Rinnailogo.PMS186.png?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/bjw5z2ex3z/web/Rinnailogo.PMS186.png?u=vmp7gq&amp;download=true</a>
Image - Lifestyle	<a href="https://rinnai.widen.net/content/gk2hy7nfxg/web/ES309FT.B.jpg?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/gk2hy7nfxg/web/ES309FT.B.jpg?u=vmp7gq&amp;download=true</a>
Image - Right	<a href="https://rinnai.widen.net/content/tu0yvhtzww/web/EX08_Beige_Right.png?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/tu0yvhtzww/web/EX08_Beige_Right.png?u=vmp7gq&amp;download=true</a>
Installation Location	Surface Mounted
Isolation Valves Included	Yes

Attribute	Value
Kit (Yes/NO)	No
Literature - Trade Brochure	<a href="https://rinnai.widen.net/content/34fuwxtxsw/original/FRENCH%20Direct%20Vent%20Wall%20Furnace%20brochure.pdf?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/34fuwxtxsw/original/FRENCH%20Direct%20Vent%20Wall%20Furnace%20brochure.pdf?u=vmp7gq&amp;download=true</a> , <a href="https://rinnai.widen.net/content/vdcwykxae/original/Direct%20Vent%20Wall%20Furnace%20Flyer%20-%20D-Series.pdf?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/vdcwykxae/original/Direct%20Vent%20Wall%20Furnace%20Flyer%20-%20D-Series.pdf?u=vmp7gq&amp;download=true</a> , <a href="https://rinnai.widen.net/content/kqfl2r2r5f/original/2021188.CA%20-%20DV%20materials%20update%20Final%20V4.pdf?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/kqfl2r2r5f/original/2021188.CA%20-%20DV%20materials%20update%20Final%20V4.pdf?u=vmp7gq&amp;download=true</a>
Manufacturer	Rinnai America Corporation
Minimum Order Qty	1.0
MSDS (Y/N)	No
Number of Heat Settings	Variable
ORMD Y/N	No
Pallet Depth (inches/cm)	48 in / (122 cm)
Pallet Height (inches/cm)	66 in / (168 cm)
Pallet Quantity	10.0
Pallet Weight (lb/kg)	515 lb / (233.6 kg)
Pallet Width (inches/cm)	40 in / (102 cm)
Product Catalog Title (SEO)	Rinnai EX11DTN Direct Vent Wall Furnace, Energy Saving Natural Gas Indoor Space Heater Wall Furnace, 11,000 BTU, Beige
Product Class	Direct Vent Wall Furnaces
Product Code	RHFE-266FTA-N
Product Depth	10.1 in / (257 mm)
Product Description - Long	EX11DTN is a quick, flexible installed, ductless, natural gas, direct vent wall heater from Rinnai; the perfect supplemental or specific zone heating solution that seeks out cold spots and within seconds begins to gently heat the room or space for maximum comfort. WiFi enabled thermostat connection ready.
Product Description - Short	Direct Vent Wall Heater DT Series
Product Group	Venting Products
Product Height	27.4 in / (695 mm)
Product Info Document - Owners Installation and Operation Manuals	<a href="https://rinnai.widen.net/content/a1ttarqod/original/200000083%20EX08DT%20and%20EX11DT%20Installation%20and%20Operation%20Manual_ENGLISH.pdf?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/a1ttarqod/original/200000083%20EX08DT%20and%20EX11DT%20Installation%20and%20Operation%20Manual_ENGLISH.pdf?u=vmp7gq&amp;download=true</a> , <a href="https://rinnai.widen.net/content/qornh240ty/original/200000097%20EX08DT%20and%20EX11DT%20Installation%20and%20Operation%20Manual-French.pdf?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/qornh240ty/original/200000097%20EX08DT%20and%20EX11DT%20Installation%20and%20Operation%20Manual-French.pdf?u=vmp7gq&amp;download=true</a> , <a href="https://rinnai.widen.net/content/gr30xz73no/original/200000083-Sp%20EX08DT%20and%20EX11DT%20Installation%20and%20Operation%20Manual.pdf?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/gr30xz73no/original/200000083-Sp%20EX08DT%20and%20EX11DT%20Installation%20and%20Operation%20Manual.pdf?u=vmp7gq&amp;download=true</a> , <a href="https://rinnai.widen.net/content/qkhapyccsi/original/200000083-Fr%2801%29%20EX08DT%20and%20EX11DT%20Installation%20and%20Operation%20Manual_FRENCH.pdf?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/qkhapyccsi/original/200000083-Fr%2801%29%20EX08DT%20and%20EX11DT%20Installation%20and%20Operation%20Manual_FRENCH.pdf?u=vmp7gq&amp;download=true</a> , <a href="https://rinnai.widen.net/content/2q3x1yrfph/original/200000098%20EX08DT%20and%20EX11DT%20Installation%20and%20Operation%20Manual-Spanish.pdf?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/2q3x1yrfph/original/200000098%20EX08DT%20and%20EX11DT%20Installation%20and%20Operation%20Manual-Spanish.pdf?u=vmp7gq&amp;download=true</a>
Product Info Document - Specification Sheets	<a href="https://rinnai.widen.net/content/ht1ulvlo5r/original/200000092-Fr%20EX08DT%20and%20EX11DT%20Specification%20Sheet.pdf?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/ht1ulvlo5r/original/200000092-Fr%20EX08DT%20and%20EX11DT%20Specification%20Sheet.pdf?u=vmp7gq&amp;download=true</a> , <a href="https://rinnai.widen.net/content/6rbvibnnor/original/200000092%20EX08DT%20and%20EX11DT%20Specification%20Sheet.pdf?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/6rbvibnnor/original/200000092%20EX08DT%20and%20EX11DT%20Specification%20Sheet.pdf?u=vmp7gq&amp;download=true</a>
Product Info Document - Warranty	<a href="https://rinnai.widen.net/content/fhqlnjw4em/original/200000078_Warranty_Direct%20Vent.pdf?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/fhqlnjw4em/original/200000078_Warranty_Direct%20Vent.pdf?u=vmp7gq&amp;download=true</a>

Attribute	Value
Product Returnable Y/N	Yes
Product Series	EnergySaver
Product Status	Active
Product Sub Series	DT
Product Weight	42 lb / (19 kg)
Product Width	18.1 in / (465 mm)
Prop 65 Warning Required	Yes
Prop 65 Warning Statement	California law requires this notice to be provided: California Proposition 65: This product can expose you to chemicals including Di (2-ethylhexyl) phthalate (DEHP) and carbon bisulfide which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, visit <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> .
Publish to RAC Staging	Yes
Publish to RAC Website	Yes
Sellable Country	US/CAN
Shipping Height (inches/cm)	30.7 in / (780 mm)
Shipping Length (inches/cm)	21.9 in / (555 mm)
Shipping Weight (lbs/kg)	53 lb / (24 kg)
Shipping Width (inches/cm)	17.5 in / (445 mm)
UL Listed	No
UPC Code	766156016547
Venting diameters	35mm
Venting Material	Stainless Steel
Venting Type	Concentric
Video - 360 Spin	<a href="https://rinnai.widen.net/content/cjtglbkc0z/original/3199_EX08Beige_Rotate.mp4?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/cjtglbkc0z/original/3199_EX08Beige_Rotate.mp4?u=vmp7gq&amp;download=true</a>
Video - Feature and Benefit	<a href="https://rinnai.widen.net/content/txy51rycdn/original/Home%20Heating%20Wisdom%20Heating%2060s.mp4?u=vmp7gq&amp;download=true">https://rinnai.widen.net/content/txy51rycdn/original/Home%20Heating%20Wisdom%20Heating%2060s.mp4?u=vmp7gq&amp;download=true</a>
Warranty - Standard for Residential	2 Years on Labor / 5 Years on Parts / 10 Years on Heat Exchanger
WiFi Capable / Compatible	No